## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

Claims 1-64 (Canceled)

65. (Currently Amended) A method of broadcasting, comprising:

providing a service ID <u>from an issuer</u> to identify a broadcast service wherein the service ID uniquely identifies a broadcast service among one or more broadcast services from a common content server on a common radio channel, <u>and further identifies availability of the broadcast service in an adjacent sector;</u>

sending the service ID to a base station;

configuring a broadcast service parameters message at the base station that includes the service ID;

transmitting the broadcast service parameters message to a mobile station; and using the service ID in the broadcast service parameters message at the mobile station to determine the availability of the broadcast service in the [[an]] adjacent sector.

- 66. (Canceled)
- 67. (Previously Presented) The method as in claim 65, wherein the broadcast service has a service name.
- 68. (Previously Presented) The method as in claim 67, further comprising requesting by the content server the service ID from a global issuer.
- 69. (Previously Presented) The method as in claim 67, wherein the service ID is a globally unique service ID issued by a global issuer.

- 70. (Previously Presented) The method as in claim 69, wherein the service ID comprises a BCMDS\_ID.
- 71. (Previously Presented) The method as in claim 70, further comprising associating an IP multicast address and UDP port number with the BCMCS\_ID.
- 72. (Previously Presented) The method as in claim 69, further comprising dynamically generating a BCMCS\_ID and associating a lifetime value with the BCMCS\_ID.
- 73. (Previously Presented) The method as in claim 67, further comprising requesting by the content server the service m from a local issuer.
- 74. (Previously Presented) The method as in claim 67, wherein the service ID is a locally unique service ID issued by a local issuer.
- 75. (Previously Presented) The method as in claim 74, wherein the service ID comprises a BCMDS\_ID
- 76. (Previously Presented) The method as in claim 75, further comprising associating an IP multicast address and UDP port number with the BCMCS ID.
- 77. (Previously Presented) The method as in claim 74, further comprising dynamically generating a BCMCS\_ID and associating a lifetime value with the BCMCS\_ID.
- 78. (Previously Presented) The method as in claim 65 wherein the service ID comprise a BCMCS\_ID.
- 79. (Previously Presented) The method as in claim 78, wherein the BCMCS\_ID is a dual BCMCS\_ID comprising a global indicator to indicate uniqueness of the BCMCS\_ID.

80. (Currently Amended) A method of broadcasting from a base station, comprising: receiving from an issuer a first broadcast service identified by a first service ID, wherein the first service ID uniquely identifies a broadcast service among one or more broadcast services from a content server on a common radio channel;

receiving from the issuer a second service ID that identifies a second broadcast service received by a neighboring base station sector, wherein the second service ID uniquely identifies a broadcast service among one or more broadcast services from a content server on a common radio channel;

configuring neighbor configuration data that relates to the second broadcast service;

configuring a broadcast service parameters message that includes the second service ID and the neighbor configuration data; and

transmitting the broadcast service parameters message to a mobile station currently receiving the first broadcast service.

## 81. (Canceled)

- 82. (Previously Presented) The method as in claim 80, wherein the fast service ID was provided by a global issuer.
- 83. (Previously Presented) The method as in claim 80, wherein the first service ID is a globally unique service ID issued by a global issuer.
- 84. (Previously Presented) The method as in claim 80, wherein the first service ID comprises a first BCMCS\_ID and wherein the second service ID comprises a second BCMCS ID.
- 85. (Previously Presented) The method as in claim 84, wherein an IP multicast address and a UDP port number are associated with the first BCMCS ID.
- 86. (Previously Presented) The method as in claim 80, wherein the first service ID has an associated lifetime value.

87. (Previously Presented) The method as in claim 80, wherein the first service ID is a

locally unique service ID issued by a local issuer.

88. (Previously Presented) The method as in claim 87, wherein the first service ID

comprises a first BCMCS\_ID.

89. (Previously Presented) The method as in claim 88, wherein an IP multicast

address and a UDP port number are associated with the first BCMCS\_ID.

90. (Previously Presented) The method as in claim 80, wherein the first service ID

comprise a first BCMCS ID.

91. (Previously Presented) The method as in claim 90, wherein the first BCMCS ID

is a dual BCMCS ID comprising a global indicator to indicate uniqueness of the first

BCMCS ID.

92. (Currently Amended) A method of receiving a broadcast at a mobile station,

comprising:

receiving a first broadcast service identified by a first service ID from a first base station

sector, wherein the first service ID uniquely identifies a broadcast service among one or more

broadcast services from a content server on a common radio channel;

receiving a broadcast service parameters message that includes a second service ID,

wherein the second service ID uniquely identifies a broadcast service among one or more

broadcast services from a content server on a common radio channel, and neighbor configuration

data, wherein the second service ID identifies a second broadcast service available from a second

base station sector, the first and second service IDs being received from a common issuer;

examining the neighbor configuration data that relates to the second broadcast service;

and

Page 5 of 12

determining, based on the neighbor configuration data, whether the first service ID and the second service ID identify the same broadcast content whereby reception of the broadcast content is continued in the second base station sector.

93. (Canceled)

94. (Previously Presented) The method as in claim 92, wherein the first service ID was provided by a global issuer.

95. (Previously Presented) The method as in claim 92, wherein the first service ID is a globally unique service ID issued by a global issuer.

96. (Previously Presented) The method as in claim 92, wherein the first service ID comprises a first BCMCS\_ID and wherein the second service ID comprises a second BCMCS\_ID.

97. (Previously Presented) The method as in claim 96, wherein an IP multicast address and a UDP port number are associated with the first BCMCS ID.

- 98. (Previously Presented) The method as in claim 92, wherein the first BCMCS\_ID has an associated lifetime value.
- 99. (Previously Presented) The method as in claim 92, wherein the first service ID is a locally unique service ID issued by a local issuer.
- 100. (Previously Presented) The method as in claim 92, wherein the first service ID comprises a first BCMCS\_ID.
- 101. (Previously Presented) The method as in claim 100, wherein the first BCMCS\_ID is a dual BCMCS\_ID comprising a global indicator to indicate uniqueness of the first BCMCS\_ID.

102. (Canceled)